PLANTMAN®



P800 SERVICE TRAILER | ST122

PRODUCT SUMMARY

P800 Service Module Specifications:

TANK #	TANK TYPE	TANK CAPACITY
No 1	Oil 15 m x ½" Spring Retractable Reel, Hose & Dripless Hand Piec	200 litres
No 2	Oil reel, hose, handpiece, fast and top fill	200 litres
No 3	Oil reel, hose, handpiece, fast and top fill	200 litres
No 4	Water reel, hose, handpiece, fast and top fill	200 litres

*GVM: Gross Vehicle Mass

P800 SERVICE TRAILER SPECIFICATIONS:

- Dual Axle 8 x 5 Trailer
- Diaphragm Pump for Waste Oil & Coolant
- Stub Pump's for New Oils
- Tank Fill from top of tanks via camlocks, with tank level gauges for new fluid tanks
- · All pumps pneumatically operated via Air manifold
- Pumps & Reels located in Gullwing Door Type Storage Box`
- Rear LED Lights Trailer Plug Number Plate Light
- Wheel Chocks Wheel Nut Indicators Spare Tyre
- · Painted in two pac white
- 2.0 kg Fire Extinguisher (mounted)
- Diesel Piston Compressor 20cfm, electric start/stop, battery & Safety valve certification
- Emergency Stop on Compressor
- 20kg HP Grease Kit (replaceable drum style) with Spring Retract Reel
- Operating and Safety Signage Decals
- Tested and Commissioned
- WA Road Licensed

APPLICATIONS:

- Open Cut Mining
- Civil Construction
- Drill Support Truck

FEATURES

- Zero spillage concept
- Robust construction
- Hazard reduction design
- User friendly operation
- Low running cost

PRODUCT SPECIFICATIONS

VOLUME	800L
ТҮРЕ	Service Trailer
MODEL	P800